

Mounting plate insulating material



Description

Order no.

Mounting plate made from insulating material, incl. fixing screws

	Enclosure type	
AK MPI 1	AKL/AKi 1-4	795 001 01
AK MPI 2	AKL/AKi 2-4	795 002 01
AK MPI 3	AKL/AKi 3-4	795 003 01
AK MPI 4	AKL/AKi 4	795 004 01

Mounting plate stainless steel



Mounting plate made from stainless steel, incl. fixing screws

	Enclosure type	
AK MPS 2	AKL/AKi 2-4	795 012 01
AK MPS 3	AKL/AKi 3-4	795 013 01
AK MPS 4	AKL/AKi 4	795 014 01

Standard rail NS 35



Standard rail acc. to DIN EN 60715, 35 x 7.5, width 35 mm

AK NS35-250 from 300 x 300 mm, length 250 mm, including spacers		562 735 01
NS35-216/3 universal floor fixing, length 216 mm, with fixing screws		795 030 01
AK NS35-406 universal floor fixing, incl. fixing screws, length 406 mm		795 045 01
AK NS35-556 universal floor fixing, incl. fixing screws, length 556 mm		795 060 01

Support for standard rails



Carrier for standard rails acc. to DIN EN 60715, 35 x 7.5 mm, set = 10 pcs.

	Height	
TR NS35-20	20	795 020 01
TR NS35-34	34,5	795 034 01
TR NS35-42	42,5	795 042 01
TR NS35-58	58,5	795 058 01
TR NS35-64	64	795 064 01
TR NS35-91	91	795 091 01

Carrier NS fixing screws



fixing screws for 1 TR NS35-xx, set of 30 pieces

SR NS35 Fixing screws for 1 support set TR NS35/xx		795 413 01
---	--	------------

KF 12 hinged window
228 x 80 mm



IP65

Description

Hinged window, for fitting to enclosure cover, for maximum 12 distribution units à 17.5 mm, with transparent hinged window, frame with sealing on both sides, with drilling template and fixing screws

Order no.

KF 12

567 412 01

SF 12 inspection window
228 x 80 mm



IP65

Inspection window, for fitting to enclosure cover, transparent inspection glass, with drilling template and fixing screws

SF 12

568 012 01

AK combi set



IP65

Combi set, for horizontal or vertical combination of all AK enclosures from 300 x 150 mm, complete with wedge connectors and intermediate sealing for 150 and 300 mm enclosure sides, each 300 mm = 1 combi set

AK KS-IP65

791 001 01

AK combi set



IP30

Combi set without intermediate enclosure seal, for horizontal or vertical combination of all AK enclosures from 300 x 150 mm, 1 set = 10 wedge connectors

AK KS-IP30

591 100 01

Combi connector



IP54

Combi connector, for connecting enclosures, thermoplastic

KST M32

f. wall thicknesses/mm
1,5 - 4,0

193 032 01

Combi set



IP66

Description

Order no.

Combi set, for side connection of enclosures with metric entries, complete with lock nuts and intermediate wall seal inserts

	f. wall thicknesses/ mm	Thread length/mm	
KS M20	2 x 3,0	12	192 020 01
KS M25	2 x 3,0	12	192 025 01
KS M25-gro	2,0 x 8,0	22	192 026 01
KS M32	2 x 3,5	14	192 032 01

AK Mounting flange



Enclosure wall, for installation in the components of the AK enclosure system for 300 mm wide end walls, with cable covers as standard

AK ABF 1 795 048 01
with pre-embossing, 2 x M32 / M40 / M50, 1 x M40 / M50 / M63

AK ABF 2 795 050 01
Smooth for self-drilling

AKi Mounting flange



Enclosure wall, for attachment to components of AKi enclosure system to 300 mm wide sides, with cable covers as standard

AKi ABF 1 796 051 01
with pre-embossing, 2 x M32 / M40 / M50, 1 x M40 / M50 / M63

AKi ABF 2 796 050 01
Smooth for self-drilling

Padlock kit



Padlock kit for upgrading the housing cover to lockable hinged door, incl. padlock, 2 hinges, fixing screws, cover plugs and drilling template

VSG 190 100 01
from TK PS/PC 1811 onwards (except TK PS/PC 1813-9 and TK PS/PC-f) and AKL/AKi 1

Hinge set



External hinge set for retrofitting the enclosure cover to hinged door, incl. 2 hinges, fixing screws, cover plugs and drilling template

ASS-gro 190 005 01
External hinge set large, from TK PS/PC 1811 (except TK PS/PC 1813-9 and TK-f) and from AKL/AKi 1

Partition wall



Description

Order no.

Partition wall, for installation in the components of the AK enclosure system, from AK 28 / AKL 2 / AKi 2, universal application for various enclosure heights, with break-out openings, grey

AK TW

797 910 01

AK External attachment set



External fixing lugs, for mounting separate enclosures or small units on flat wall surfaces, can be fixed to the box base at an angle of 0°, 45°, or 90°, wall gap 7 mm, material stainless steel, suitable for all AK enclosures from 300 mm front,

AK ABL-ES
Set = 4 pcs.

793 004 01

Z-wall profile



Z-wall profile, length 2 m, with 8 M6 cylinder screws and 8 captive push nuts, wall clearance 70 mm, material: galvanised steel

ZPR

070 800 01